

CLIT10-WS



Features

- 10.25" High brightness LCD display
- SoC platform
- Auto dimming design
- Signal fusion: Camera, T-Box, Sensor
- Connectivity: Bluetooth & Wi-Fi
- Interface: CANBUS & UART
- IP67 design for harsh environment

Specification

Description	Specification
Processor	ARM 800MHz, Dual RISC 300MHz
Image resolution	1280 x 480 pixels
Working voltage	DC 9V ~ 16V
Connectivity	Bluetooth & Wi-Fi
Quiescent Current	≤ 1mA
FW update	CANBUS
Supporting Video input	Yes
Operating temperature	-20°C ~70°C (+32°F~158°F)
Non-Operating temperature	-30°C ~ 85°C (-22°F~185°F)
Supporting accessory	DVR, Camera, Sensor, T-Box

Cluster Features

- ✓ Start-up animation
- ✓ Current vehicle speed
- ✓ Tell-tale indicator
- ✓ Lamp
 - Left/Right turn
 - High/Low beam
- ✓ Mileage
- ✓ Smart key
- ✓ Temperature
- ✓ Clock
- ✓ Gear (D/N/R)
- ✓ Service timing light
- ✓ Warning messages
- ✓ CVBS in
- ✓ Battery
- ✓ Multi-languages

Value-added Function (Optional)

- I. ADAS Service
 - ✓ BSD (Radar sensor)
 - ✓ Front & Rear DVR
 - ✓ AVAS (Acoustic vehicle alert system)
- II. Smart phone application (3rd APP)
 - ✓ Turn by Turn Navigation
 - ✓ Missing call
 - ✓ Cluster menu control
 - ✓ Screen mirroring
 - ✓ Personalization setting